40% П COST



The UL/CSA-listed BrandTech PDU uses a single installation to manage up to 200 amps of input and distribute it to three outputs of 480V, 60 amps each.







Advantages

- A single PDU can be used with multiple machines in applications ranging from industrial painting to welding.
- It is fully insulated and resistant to shock, impact and corrosion, and includes embedded lockout/ tagout levers.
- 30-milliamp ground-fault circuit interrupter (GFCI) for improved safety.
- The breakers are mounted under a hinged window for easy access and improved safety.
- > Each machine is plugged into a separate port with its own circuit breaker, making it easy to know which one to shut down in an emergency.

☑ UL/CSA Listed

The PDU went through UL (Underwriters Laboratories) and CSA Group (a global organization dedicated to safety) testing and was listed under UL 1640 and CSA C22.2. No. 14-13 certifications.

Enclosure is designed to protect components in an outdoor environment.

See how the BrandTech® PDU can reduce complexity and increase equipment savings. Contact us today at **800 558 4772** or by filling out our contact us form at **www.BrandSafway.com/contacts.**

BrandSafway provides a full range of access and industrial services.

Ready to Deliver











BrandSafway Global Support Center 600 Galleria Parkway SE, Suite 1100 Atlanta, GA 30339 Toll free: 800 558 4772

