
WC Series Sidewalk Canopy Product Selection Guide





Pre-Engineered For Easy Installation

- Meets local, state and federal codes for protection from construction debris
- Adjusts to match sloping sidewalks
- Compatible with standard I-Beams as well as standard BrandSafway components and accessories
- Supports scaffold structures

WC Series Sidewalk Canopy

Bill of Material for 8' High Sidewalk Canopy with Two 8' Long Bays

Qty.	Part No.	Description
4	WC8	8' Column with hardware
2	WC8J	8' Column with jack and hardware
2	WDB8	Diagonal Brace
2	WSC	Swivel Clamp
8	WHB8	8' Horizontal Brace
3	W8 x 10 x 8'	Steel Beam
14	ALJ-11	Aluminum Joist, 11'
12	WBC	Beam Clamp
28	ABC	Aluminum Beam Clamp
24		2" x 10" x 8' Plank
6		2" x 10" x 3' Sills
20		2" x 10" x 10' Plank
2		4' x 8' x 5%" Plywood
10		2" x 4" x 5' 5¾" (Ends at 45°)
4		2" x 4" x 8' Sill Plates
10		2" x 4" x 45" Studs
		Nails for 2 x 4 and Plywood

Additional Available Components

Part No.	Description	
WC10	10' Column with Hardware	
WC12	12' Column with Hardware	
WC16	16' Column with Hardware	
WHB4	Horizontal Brace, 4'	
WHB6	Horizontal Brace, 6'	

All drawings on this sheet are for illustrative purposes only. This sheet is intended for general information purposes only. Because of the many variables which affect the performance of the product line, some of the information in this brochure may not apply. For specific applications, contact BrandSafway.

Note: All scaffolds shall be erected, modified and dismantled only under the supervision of a Competent Person. Erection, use, maintenance and disassembly must conform to current manufacturer's instructions as well as all federal, state, provincial and local regulations. Copies of complete Safety Guidelines for these and other products are available from BrandSafway without charge.

Brand Industrial Services, Inc.

1325 Cobb International Dr. Ste A-1 Kennesaw, GA USA 30152

Toll free: 800 558 4772

For more information, visit our website at www.brandsafway.com

©2018 All rights reserved.